

Level probe type EL19-2

Application and function

The level probe EL19-2 in connection with the controller SMLC1 is a self-monitoring low water level limiter of special construction as per DIN EN 50156-1 and the German rule "Wasserstand 100".

Technical basic equipment


Mechanical connection	G ½ (SW27)	
Electrical connection	Plug connection with screw terminals, traction relief	
Material	Probe housing	stainless steel
	Probe rod	stainless steel
	Probe extension	stainless steel
	Insulator	Ceramic
	Socket	Polyamid
	Sealing ring	Soft iron



Technical data

Component mark	TÜV • ID : 00000006173					
EG-component test	CE 0035-BN0104					
Allowable pressure	PS [bar]	50	80	100	160	200
Allowable temperature	TS [° C]	265	296	312	346	367
Cable gland	M16x1,5					
Protection as per DIN VDE 0470	IP65					
Allowable pressure on plug	100° C					

Dimension Y [mm] min. 150		
1700	with protection tube > DN80	vertical installation position
800	with protection tube DN50	vertical installation position
800	with protection tube DN50/100	inclined installation up to 45°



The component mark is only valid:

- For standpipes: if shutoff valves have been installed between connection flanges and boiler nozzles. A drain valve is also required
- For nozzles: if boiler nozzle corresponds to the construction according to data sheet D-08-D-16351-0.
- Protection tube K, flanges, screws, nuts and sealings can be delivered too.
- For probe installation see data sheet D-08-D-16352-0



- Baumuster geprüft
- EG Baumuster geprüft
- Fertigung überwacht

